

WE MAKE THINGS LAST	HARDSCAPE STONE APPLICATION GUIDE*					
	PROTECTION	PROTECTION COLOR ENHANCE	PROTECTION MAXIMUM STAIN RESISTANCE	PROTECTION PREVENTS EFFLORESCENCE	PROTECTION PREVENTS EFFLORESCENCE	PROTECTION HD WATER AND OIL REPELLENT
PRODUCT	ROCKSTEEL RS100	ULTRA POROUS RS500	STAIN SAFE RS600	NATURAL STONE SEAL NS200	POROUS PRO PLUS NS800	STAIN PRO MAX NS900
TYPE BASE	SOLVENT	SOLVENT	SOLVENT	WATER	WATER	WATER
TYPE STONE	GENERAL	POROUS	GENERAL	GENERAL	POROUS	GENERAL
COVERAGE RATE - SQ.FT./GAL	200-500SF	175-300SF	200-400SF	200-400SF	175-300SF	175-350SF
FLAGSTONE POROUS	✓	✓✓	✓	✓✓	✓	✓
FLAGSTONE DENSE	✓		✓	✓		
LIMESTONE		✓	✓	✓✓	✓✓	✓
MOSS ROCK	✓	✓✓	✓	✓	✓✓	✓
NATURAL STONE	✓	✓	✓	✓	✓	✓
PENNSYLVANIA BLUE	✓		✓	✓✓	✓	✓
SLATE	✓✓	✓	✓	✓✓	✓	✓
TRAVERTINE OUTSIDE	✓	✓	✓	✓✓		
TRAVERTINE INSIDE	✓	✓	✓	✓		✓
SANDSTONE		✓✓	✓		✓✓	✓
CANTERA		✓✓	✓		✓✓	✓
RIVER ROCK	✓		✓	✓		
MARBLE			✓✓			✓
GRANITE			✓✓			✓
QUARTZITE	✓		✓✓			✓
MORTOR / GROUT	✓	✓	✓	✓	✓	✓
PAVERS				✓	✓	✓✓
PLASTER		✓		✓	✓	
STUCCO		✓		✓	✓	
CONCRETE		✓		✓	✓	✓
NON GAZED BRICK	✓	✓	✓	✓	✓	✓
ARTIFICIAL STONE	✓	✓	✓	✓	✓	✓
POROUS TILE	✓	✓✓	✓	✓	✓✓	✓
DENSE TILE	✓		✓	✓		✓
SLATILLO TILE	✓	✓	✓	✓	✓	✓
ERODED/FLAKING STONE					✓	

\*NOTE: SEVERAL PRODUCTS CAN BE APPLICABLE SEALERS FOR A PARTICULAR STONE - REFER TO APPLICATION GUIDE FOR EACH PRODUCTS DETAILS

✓✓

IS THE RECOMMENDED CHOICE FOR THE STONE TYPE - ALWAYS TEST IN AN INCONSPICUOUS AREA PRIOR TO APPLICATION